



(19)

(11) Publication number: **61**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **59252121**(51) Intl. Cl.: **B41M 3/12 B41F 16/00 B44**(22) Application date: **29.11.84**

(30) Priority:

(43) Date of application
publication: **17.06.86**(84) Designated contracting
states:(71) Applicant: **KIYUUBITSUKU ENG**(72) Inventor: **NAKANISHI MOTOYA
OTAKI NOBUYUKI**


(74) Representative:

(54) PRINTING METHOD

(57) Abstract:

PURPOSE: To provide a printing method wherein a masking film is dissolved simultaneously with the dissolution of a transfer piece, by using a film equipped with swellability and water-solubility as said transfer piece and forming the masking film by coating a water-soluble masking agent.

CONSTITUTION: A water-soluble masking layer 9 is formed to the entire surface of an article 4 to be printed having a masking piece 8 placed to the printed part 4a thereof and the masking piece 8 is subsequently removed along with the masking layer 9a to leave a masking film 9b only on a printing unnecessary part 4b. The article 4 to be printed, which received masking treatment, is sunk in water and the transfer piece 7 is closely adhered to the article 4 to be printed by water pressure. Because a transfer pattern



6, for example, a grain pattern is printed on the transfer piece 7, the transfer pattern 6 is applied to the article 4 to be printed by transfer printing but, because the transfer piece 7 is water-soluble, said transfer piece 7 disappears during transfer and the masking film 9b is also dissolved through the contact with water to partially leave the transfer pattern 6 to the surface of the article to be printed.


COPYRIGHT: (C)1986,JPO&Japio



Intellectual Property Network



[Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)



P61130081A2: PRINTING METHOD

[View Images \(1 pages\)](#) | [View INPADOC only](#)

Country: **JP Japan**

Kind:

Inventor(s): **NAKANISHI MOTOYASU
OTAKI NOBUYUKI**

Applicant(s): **KIYUUBITSUKU ENG:KK**
[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **June 17, 1986 / Nov. 29, 1984**

Application Number: **JP1984000252121**

IPC Class: **B41M 3/12; B41F 16/00; B44C 1/16**

Abstract:

Purpose: To provide a printing method wherein a masking film is dissolved simultaneously with the dissolution of a transfer piece, by using a film equipped with swellability and water-solubility as said transfer piece and forming the masking film by coating a water-soluble masking agent.

Constitution: A water-soluble masking layer 9 is formed to the entire surface of an article 4 to be printed having a masking piece 8 placed to the printed part 4a thereof and the masking piece 8 is subsequently removed along with the masking layer 9a to leave a masking film 9b only on a printing unnecessary part 4b. The article 4 to be printed, which received masking treatment, is sunk in water and the transfer piece 7 is closely adhered to the article 4 to be printed by water pressure. Because a transfer pattern 6, for example, a grain pattern is printed on the transfer piece 7, the transfer pattern 6 is applied to the article 4 to be printed by transfer printing but, because the transfer piece 7 is water-soluble, said transfer piece 7 disappears during transfer and the masking film 9b is also dissolved through the contact with water to partially leave the transfer pattern 6 to the surface of the article to be printed.

COPYRIGHT: (C)1986,JPO&Japio

Other Abstract Info:

none

Foreign References:

(No patents reference this one)

Powered by **DB2**
and **Net Data**

**Nominate this
invention
for the Gallery...**

Alternative
Searches



[Patent Number](#)



[Boolean Text](#)



[Advanced Text](#)

Browse



[U.S. Class
by title](#)



[U.S. Class
by number](#)



[IBM Technical
Disclosure Bulletin](#)

BEST AVAILABLE COPY